

# KERB MARKING PAINT

ALCOLite

“Where Durability Meets Visibility”

Eco-Friendly, Quick-Drying Kerb Marking Acrylic Resin-based Paint



**Category : Water-based Paint**

**Application :** Specially formulated for all types of **traffic kerbs/footpath** to enhance **visibility and safety**



## **METHOD OF APPLICATION**

- Water based paint can be applied using a brush, roller, or sprayer.
- Ensure air and surface temperature is above 10°C.
- Avoid application if humidity is above 85%, temperature is falling, or rain is imminent.
- Clean the surface thoroughly before application.
- Stir well before use.
- Apply one coat at recommended wet film thickness (0.150 mm).
- For a second coat, allow 2-3 hour gap.
- On new surfaces, use a recommended primer before application.
- Open the paint container and mix thoroughly using a hand mixer or stir stick. Alternatively, keep the container upside down for a few hours before use.

## **ALCOLITE INDIA ROAD SAFETY PVT. LTD.**

**Registered Office :** H-14, DSIIDC Industrial Complex, Udyog Nagar, Rohtak Road, Nangloi, Delhi-110041

**Factory Address :** Plot No. E1-1129, RIICO Industrial Area, Bandapur, Alwar, Rajasthan - 301707



[www.alcolite.in](http://www.alcolite.in)



[customercare@alcolite.in](mailto:customercare@alcolite.in)



+91-8877005757

*“Where Durability Meets Visibility.”*

## KEY BENEFITS

- **Form & Condition** - Smooth & flowing viscous liquid
- **Eco-friendly** – Water-based, no thinner required (only water needed)
- **Fast Drying** – Touch dry in 10–20 minutes, hard dry in 45 minutes (depending on weather)
- **Easy Application** – Suitable for airless spray, roller, or brush
- **Easy Maintenance** – Tools can be cleaned with water and mild detergent
- **High Visibility** - Bright, durable colours for traffic kerbs & footpaths, like eggshell finish
- **Safe & Reliable** - Designed for long-lasting road safety markings
- **Weather Resistant** - Performs well against rain, heat, and UV exposure

## TECHNICAL DETAILS

- **Colours Available:** White, Yellow, Red, Blue, Green, Black & more
- **Recommended Film Thickness:** 0.150 mm (wet)
- **Coverage:** 6–8 m<sup>2</sup>/litre, Single Coat (varies with kerb porosity and surface profile)
- **Specific Gravity (SG):** 1.3 approx
- **Application Temperature:** Minimum 10°C
- **Application Humidity:** Maximum 85%
- **Drying Time:** 10- 15 minutes (touch dry)

## PACKAGING DETAILS

- **Available Sizes** – 1L | 4L | 10L | 20L
- **Net Quantity** – 20 Litres
- **Gross Quantity** – 27 kgs

## MISTAKES

- Painting in direct sun/heat
- Starting second coat too soon
- Skipping primer on stains

